SAFETY DATA SHEET

MATERIAL IDENTIFICATION SECTION 1

Product:

EMAGES TO FABRIC

Date Prepared:

Manufacturer:

8/10/2020

Importer -

The Adhesive Products. Inc

18/10 Pioneer Avenue, Thornleigh NSW 2120

S&S Wholesale Pty. Limited

520 Cleveland Ave

Tel: 1300 731 529

Fax: 1300 739 715

Albany, CA 94710

Telephone Number:

510-526-7616 (8am-5pm M-F)

Emergency Contact:

S&S Wholesale Pty. Limited

Tel: 1300 731 529

Fax: 1300 739 715

COMPOSITION/INFORMATION ON INGREDIENTS SECTION 2

Substances listed below are reportable hazardous ingredients as defined by the OSHA Hazard Communication Standard 29CFR1910.1200.

This product is not hazardous as defined in 29CFR1910.1200.

HEALTH HAZARDS SECTION 3

Primary Routes of Exposure:

Inhalation Skin Contact

Inhalation:

Inhalation of vapor or mist can cause mild irritation of nose, throat, and lungs.

Eye Contact:

Direct contact with the material can cause slight irritation.

Skin Contact:

Prolonged or repeated skin contact can cause slight skin irritation.

Ingestion:

Not an anticipated route of exposure. Available data indicate a low odor of toxicity. Excessive quantities may cause irritation of digestive tract.

Medical Conditions Generally Aggravated By Exposure

None known

Carcinogens Under OSHA, ACGIH, NTP, IARC, Other:

This product contains no carcinogens as defined in 29CFR1910.1200.

SECTION 4 FIRST AID

Inhalation:

Move subject to fresh air.

Eye Contact:

Flush eyes with large amount of water for at least 15 minutes. Seek medical advice if irritation persists.

Ingestion:

If swallowed give 2 glasses of water to drink. Seek medical attention. Never give anything by mouth to an unconscious person.

Skin Contact:

Wash affected area with soap and water.

SECTION 5 FIRE AND EXPLOSION DATA

Flash Point Noncombustible

Auto-ignition Temperature Not Applicable

Lower Explosive Limit Not Applicable

Upper Explosive Limit Not Applicable

Extinguishing Agents:

For dry polymer use water or carbon dioxide. Product does not burn. Aqueous mixture is not flammable.

Personal Protective Equipment:

Wear self-contained breathing apparatus (pressure-demand MSHA/NIOSH approved or equivalent) and full protective gear.

Unusual Hazard:

Product can spatter above 100°C./212°F. Dried product can burn. Water, carbon dioxide, carbon monoxide, and smoke are produced.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Protection:

Appropriate protective equipment must be worn when handling a spill of this product. See SECTION 8, EXPOSURE CONTROLS/PERSONAL PROTECTION for recommendations.

Containment:

Stop the leak. Remove any ignition sources. Ventilate the area. Construct a dike of inert material (sand, earth) to prevent spread.

Clean-up Procedures:

If recovery is not possible, mix with dry soil, sand or non reactive absorbent (sodium chloride) and transfer to suitable containers for recovery or disposal. Wash contaminated property quickly before product dries. Flush area with water spray. Keep clean-up run off from municipal sewers or open bodies of water.

Special Notes:

Spilled product is slippery. Use caution and avoid falls.

SECTION 7 HANDLING AND STORAGE

Storage:

Keep from freezing.

Handling:

Avoid breathing vapors. Handle in well ventilated work area

Special Requirements

Have emergency showers and eye wash stations readily available.

SECTION 8 PERSONAL PROTECTION/EXPOSURE CONTROLS

Hazardous Ingredients:

No. WEIGHT (%) CAS NUMBER

- 1) This product is not hazardous as defined in 29CFR1910.1200.
- 2)
- 3)

Exposure Limits:				
	Units	TWA	STEL	CEILING
1) OSHA	N/A	N/A	N/A	N/A
ACGIH	N/A	N/A	N/A	· N/A
2) OSHA	N/A	N/A	N/A	N/A
ACGIH	N/A	N/A	N/A	N/A
3) OSHA	N/A	N/A	N/A	N/A
ACGIH	N/A	N/A	N/A	N/A

Eve Protection:

Chemical splash goggles (ANSI Z87.1 or approved equivalent).

Hand Protection:

Neoprene rubber gloves.

Respiratory Protection:

Not required under normal conditions. Use a NIOSH approved organic vapor respirator for severe conditions.

Protective Clothing:

No specific recommendation.

Engineering Controls:

Use local exhaust ventilation with minimum capture velocity of 100ft/min. (.5m/sec.) at the point of vapor evolution.

Other Protective Equipment:

Eyewash facility.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

SECTION 10 STABILITY AND REACTIVITY

Chemical Stability:

Stable at ambient temperatures. Freezing or boiling may cause coagulation.

Incompatibility:

Avoid mineral acids (i.e. Sulfuric, phosphoric, etc.) Avoid alkalis (i.e. sodium or potassium hydroxide).and acetic acid.

Hazardous Polymerization:

Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Please refer to Section 3, HAZARD IDENTIFICATION, for available information on potential health effects.

SECTION 12 ECOLOGICAL INFORMATION

No available data

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal:

Comply with all Federal, State, Provincial and Local Regulations. This product can be chemically or biologically degraded. If necessary a licensed waste disposal facility maybe used. The product can be incinerated, though chemical or biological treatment is sufficient.

SECTION 14 TRANSPORT INFORMATION

DOT SHIPPING NAME:

RESIN COMPOUND - Not DOT Regulated Keep From Freezing

SECTION 15 REGULATORY INFORMATION

Food and Drug Administration (FDA):

This product can be used in compliance with FDA regulation 21 CFR 175.105 Adhesives, subject to the end use extractive limitations cited in the regulation.

Toxic Substance Control Act (TSCA):

All components are included in the EPA Toxic Substance Control Act Chemical Substance inventory.

OSHA Hazard Communication Standard (29CFR1910.1200):

Hazard class is none

EPA SARA Title III Section 312 (40CFR370):

Hazard class is none

EPA SARA Title III Section 313 (40CFR372):

No toxic chemicals above the "de minimis" level.

CERCLA (40CFR302.4):

Releases of this product to air, land, or water are not reportable to the National Response Center or to local and state emergency planning committees.

Waste Classification:

If discarded as supplied this product does not meet the RCRA definition of ignitability, corrosivity, or reactivity, and is not listed in 40CFR261.33.

WHMIS HAZARD CLASSIFICATION:

None

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

California Proposition 65:

This product contains a trace component or trace components known to the state of California to cause cancer and/or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Water and toxic Enforcement Act of 1986: None Known

SECTION 16 - OTHER INFORMATION

HMIS RATING: Health 1 Flammability 0 Reactivity 0 SCALE

Severe = 4

Serious = 3

Moderate = 2

Slight = 1

Minimal = 0

Abbreviations:

ACGIH American Conference of Governmental Industrial Hygienists

ANSI American National Institute Standard
CAS Chemical Abstract Service Number

CERCLA Comprehensive Environmental Response, Compensation and Liability Act

CPR Controlled Products Regulations
DOT Department of Transportation
EPA Environmental Protection Agency

Hg Mercury

HMIS Hazardous Materials Identification System
IARC International Agency for Research on Cancer

LD Lethal Dose

mg/kg Milligram per kilogram

mm Milligram

MSDS Material Safety Data Sheet

MSHA Mine Safety and Health Administration

N/A Not Applicable

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

ppm Parts per million

SARA Superfund Amendment and Reauthorization Act

STEL Short-Term Exposure Limit
TSCA Toxic Substance Control Act

TWA Time Weighted Average

WHMIS Workplace Hazardous Materials Information System

The information and recommendations accumulated herein are, to the best of The Adhesive Products, Inc., knowledge and belief accurate and reliable as of the date issued, but is not warranted or guaranteed. The Adhesive Products, Inc. shall not be liable for any loss or damage arising out of the use thereof. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.