Trade name: Marabu Porcelain 158, 50 ml

Version: 7 / Date revised: 29.01.2020

Print date: 29.01.20 Substance number: 110505158 Replaces Version: 6 / WORLD

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Marabu Porcelain 158, 50 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

1.3. Details of the supplier of the safety data sheet

Address/Manufacturer

Marabu GmbH & Co. KG Asperger Strasse 4 71732 Tamm Germany

Telephone no. +49-7141/691-0 Fax no. +49-7141/691-147

Information provided Department product safety

by / telephone

for this SDS

E-mail address of person responsible

PRSI@marabu.com

Importer -

S&S Wholesale Pty. Limited 18/10 Pioneer Avenue, Thornleigh NSW 2120

Tel: 1300 731 529 Fax: 1300 739 715

Emergency Contact:

S&S Wholesale Pty. Limited

Tel: 1300 731 529 Fax: 1300 739 715

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification ***

2.1. Classification of the substance or mixture

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

EUH208 Contains 2-Methyl-2H-isothiazol-3-one, A mixture of:

5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and

2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1).

1,2-Benzisothiazol-3(2h)-one, May produce an allergic reaction.

Supplemental information

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Labelling according to regulation (EU) No 528/2012 ***

Contains a biocidal product: A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and 2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1)

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients ***

3.2. Mixtures

Chemical characterization

Paint based on acrylic resins and on water

Hazardous ingredients ***

Trade name: Marabu Porcelain 158, 50 ml

Version: 7 / Date revised: 29.01.2020

Substance number: 110505158 Replaces Version: 6 / WORLD Print date: 29.01.20

3-Butoxypropan-2-ol

CAS No. 5131-66-8 EINECS no. 225-878-4

Registration no. 01-2119475527-28

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Skin Irrit. 2 H315 Eye Irrit. 2 H319

1,2-Benzisothiazol-3(2h)-one

CAS No. 2634-33-5 EINECS no. 220-120-9

Concentration < 0,05 %

Classification (Regulation (EC) No. 1272/2008)

 Aquatic Acute 1
 H400

 Skin Sens. 1
 H317

 Acute Tox. 4
 H302

 Skin Irrit. 2
 H315

 Eye Dam. 1
 H318

 Acute Tox. 2
 H330

 Aquatic Chronic 2
 H411

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317 >= 0,05

Pyridin-2-thiol-1-oxide, sodium salt

CAS No. 3811-73-2 EINECS no. 223-296-5

Concentration >= 0,001 < 0,1 %

Classification (Regulation (EC) No. 1272/2008)

Eye Dam. 1 H318 Acute Tox. 4 H302 Acute Tox. 4 H332 Aquatic Acute 1 H400 Aquatic Chronic 2 H411

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1 H400 M = 100

A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and 2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1)

CAS No. 55965-84-9

Concentration < 0,001 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 2 H330
Aquatic Chronic 1 H410
Aquatic Acute 1 H400
Skin Sens. 1A H317
Skin Corr. 1C H314
Acute Tox. 2 H310
Acute Tox. 3 H301

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Corr. 1C H314 >= 0,6 Eye Irrit. 2 H319 <= 0,06 < 0,6

Trade name: Marabu Porcelain 158, 50 ml

Version: 7 / Date revised: 29.01.2020

Substance number: 110505158 Replaces Version: 6 / WORLD Print date: 29.01.20

Skin Irrit. 2 H315 <= 0,06 < 0,6
Skin Sens. 1 H317 >= 0,0015
Aquatic Acute 1 H410 M = 100
Aquatic Chronic H410 M = 100

1

2-Methyl-2H-isothiazol-3-one

CAS No. 2682-20-4 EINECS no. 220-239-6

Concentration < 0,0015 %

Classification (Regulation (EC) No. 1272/2008)

H301 Acute Tox. 3 Acute Tox. 2 H330 Skin Corr. 1B H314 Eve Dam. 1 H318 Aquatic Acute 1 H400 Skin Sens. 1A H317 Aquatic Chronic 1 H410 Acute Tox. 3 H311

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1A H317 >= 0,0015Aquatic Acute 1 H400 M = 10

SECTION 4: First aid measures

4.1. Description of first aid measures

After skin contact

Wash with plenty of water and soap. Do NOT use solvents or thinners.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). In case of irritation consult an oculist.

After ingestion

Rinse mouth thoroughly with water. If larger amounts are swallowed or in the event of symptoms take medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide, Foam, Sand, Water

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); dense black smoke

5.3. Advice for firefighters

Other information

Collect contaminated fire-fighting water separately, must not be discharged into the drains.

Trade name: Marabu Porcelain 158, 50 ml

Version: 7 / Date revised: 29.01.2020

Substance number: 110505158 Replaces Version: 6 / WORLD Print date: 29.01.20

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No particular measures required.

6.2. Environmental precautions

No particular measures required.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid skin and eye contact. Smoking, eating and drinking shall be prohibited in application area.

Advice on protection against fire and explosion

No special measures required.

Classification of fires / temperature class / Ignition group / Dust explosion class

Temperature class T4

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in frostfree conditions.

7.3. Specific end use(s)

Paint

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Other information

There are not known any further control parameters.

Derived No/Minimal Effect Levels (DNEL/DMEL)

3-Butoxypropan-2-ol

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 147 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 52 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Trade name: Marabu Porcelain 158, 50 ml

Version: 7 / Date revised: 29.01.2020

Substance number: 110505158 Replaces Version: 6 / WORLD Print date: 29.01.20

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 43 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 22 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Mode of action Systemic effects

Concentration 12,5 mg/kg/d

Predicted No Effect Concentration (PNEC)

3-Butoxypropan-2-ol

Type of value PNEC Type Soil

Concentration 0,16 mg/kg

Type of value PNEC Type Water

Concentration 0,525 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 2,36 mg/kg

Type of value PNEC Saltwater

Concentration 0,0525 mg/l

Type of value PNEC

Type Marine sediment

Concentration 0,236 mg/kg

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 10 mg/l

8.2. Exposure controls

Exposure controls

Provide adequate ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form liquid coloured

Trade name: Marabu Porcelain 158, 50 ml

Version: 7 / Date revised: 29.01.2020

Substance number: 110505158 Replaces Version: 6 / WORLD Print date: 29.01.20

Odour solvent-like

Odour threshold

Remarks No data available

pH value

Value 8 to 9

Temperature 20 °C

Method WTW PH 340

Melting point

Remarks not determined

Freezing point

Remarks not determined

Initial boiling point and boiling range

Value appr. 100 °C

Pressure 1.013 hPa

Source Literature value

Flash point

Remarks Not applicable

Evaporation rate (ether = 1):

Remarks not determined

Flammability (solid, gas)

Not applicable

Upper/lower flammability or explosive limits

Lower explosion limit appr. 0,6 %(V) Upper explosion limit appr. 20,4 %(V)

Source Literature value

Vapour pressure

Value appr. 23 hPa

Temperature 20 °C

Method Value taken from the literature

Vapour density

Remarks not determined

Density

Value 1,03 g/cm³

Temperature 20 °C

Method DIN EN ISO 2811

Solubility in water

Remarks miscible

Ignition temperature

Value appr. 189 °C

Source Literature value

Viscosity

Value 2500 to 5000 mPa.s

Temperature 20 °C

Method Brookfield

9.2. Other information

Other information

None known

Trade name: Marabu Porcelain 158, 50 ml

Version: 7 / Date revised: 29.01.2020

Substance number: 110505158 Replaces Version: 6 / WORLD Print date: 29.01.20

SECTION 10: Stability and reactivity

10.1. Reactivity

None

10.2. Chemical stability

No hazardous reactions known.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

No hazardous reactions known.

10.5. Incompatible materials

None

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity

Remarks Based on available data, the classification criteria are not met.

Acute oral toxicity (Components)

1,2-Benzisothiazol-3(2h)-one

Species rat

LD50 1193 mg/kg

Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity (Components)

1,2-Benzisothiazol-3(2h)-one

Species rat

LD50 4115 mg/kg

Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Remarks Based on available data, the classification criteria are not met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Trade name: Marabu Porcelain 158, 50 ml

Version: 7 / Date revised: 29.01.2020

Substance number: 110505158 Replaces Version: 6 / WORLD Print date: 29.01.20

Single exposure

Remarks Based on available data, the classification criteria are not met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself.Do not allow to enter drains or water courses.The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

Fish toxicity (Components)

A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and

2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1)

Species rainbow trout (Oncorhynchus mykiss)

LC50 0,188 mg/l

Duration of exposure 96 h

1,2-Benzisothiazol-3(2h)-one

Species rainbow trout (Oncorhynchus mykiss)

LC50 2,18 mg/l

Duration of exposure 96 h

Daphnia toxicity (Components)

A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and

2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1)

Species Daphnia magna

EC50 0,126 mg/l

Duration of exposure 48 h

1,2-Benzisothiazol-3(2h)-one

Species Daphnia magna

EC50 2,94 mg/l

Duration of exposure 48 h

Algae toxicity (Components)

A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and 2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1)

Trade name: Marabu Porcelain 158, 50 ml

Version: 7 / Date revised: 29.01.2020

Substance number: 110505158 Replaces Version: 6 / WORLD Print date: 29.01.20

Species Selenastrum capricornutum

EC50 0,027 mg/l

Duration of exposure 72 h

1,2-Benzisothiazol-3(2h)-one

Species Pseudokirchneriella subcapitata

ErC50 0,11 mg/l

Duration of exposure 72 h

12.2. Persistence and degradability

General information

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

The product can be placed with other household refuse. Small residues in containers can be washed-out with water and put into the drainage system.

Disposal recommendations for packaging

Packaging that cannot be cleaned should be disposed off as product waste.

Completely emptied packagings can be given for recycling.

SECTION 14: Transport information

Trade name: Marabu Porcelain 158, 50 ml

Version: 7 / Date revised: 29.01.2020

Substance number: 110505158 Replaces Version: 6 / WORLD Print date: 29.01.20

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	The product does not constitute a hazardous substance in land transport	The product does not constitute a hazardous substance in sea transport	The product does not constitute a hazardous substance in air transport
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
Subsidiary risk		-	-
Label			
14.4. Packing group	-	-	-
Transport category	0		
14.5. Environmental hazards		no	
	-		-

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

SECTION 15: Regulatory information ***

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Other information

All components are contained in the AICS inventory.

All components are contained in the DSL inventory.

All components are contained in the IECSC inventory.

All components are contained in the TSCA inventory or exempted.

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

Trade name: Marabu Porcelain 158, 50 ml

Version: 7 / Date revised: 29.01.2020

Substance number: 110505158 Replaces Version: 6 / WORLD Print date: 29.01.20

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 2 Acute toxicity, Category 2
Acute Tox. 3 Acute toxicity, Category 3
Acute Tox. 4 Acute toxicity, Category 4

Aquatic Acute 1 Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic, Category 2

Eye Dam. 1 Serious eye damage, Category 1

Eye Irrit. 2 Eye irritation, Category 2
Skin Corr. 1B Skin corrosion, Category 1B
Skin Corr. 1C Skin corrosion, Category 1C
Skin Irrit. 2 Skin irritation, Category 2
Skin Sens. 1 Skin sensitization, Category 1
Skin Sens. 1A Skin sensitization, Category 1A

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: *** This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship. The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.