



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Porcelain&GlasPainterSor.Basic 125

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Paint

1.3. Details of the supplier of the safety data sheet

Address/Manufacturer

Marabu GmbH & Co. KG
 Asperger Strasse 4
 71732 Tamm
 Germany
 Telephone no. +49-7141/691-0
 Fax no. +49-7141/691-147
 Information provided by / telephone Department product safety
 E-mail address of person responsible PRSI@marabu.com
 for this SDS

Importer -
 S&S Wholesale Pty. Limited
 18/10 Pioneer Avenue,
 Thornleigh NSW 2120
 Tel: 1300 731 529 Fax: 1300 739 715
 Emergency Contact:
 S&S Wholesale Pty. Limited
 Tel: 1300 731 529 Fax: 1300 739 715

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification ***

2.1. Classification of the substance or mixture

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

EUH208 Contains 2-Methyl-2H-isothiazol-3-one, 1,2-Benzisothiazol-3(2h)-one, May produce an allergic reaction.

Supplemental information

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients ***

3.2. Mixtures

Chemical characterization

Paint based on acrylic resins and on water

Hazardous ingredients ***

1,2-Benzisothiazol-3(2h)-one

CAS No. 2634-33-5

EINECS no. 220-120-9

Concentration < 0,05 %



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

Classification (Regulation (EC) No. 1272/2008)

Aquatic Acute 1	H400
Skin Sens. 1	H317
Acute Tox. 4	H302
Skin Irrit. 2	H315
Eye Dam. 1	H318
Acute Tox. 2	H330
Aquatic Chronic 2	H411

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1	H317	>= 0,05
--------------	------	---------

Bronopol (INN)

CAS No.	52-51-7		
EINECS no.	200-143-0		
Registration no.	01-2119980938-15		
Concentration	>= 0,01	< 0,1	%

Classification (Regulation (EC) No. 1272/2008)

Eye Dam. 1	H318
Skin Irrit. 2	H315
STOT SE 3	H335
Acute Tox. 4	H302
Acute Tox. 4	H312
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1	H400	M = 10
Aquatic Chronic 1	H410	M = 1

2-Methyl-2H-isothiazol-3-one

CAS No.	2682-20-4	
EINECS no.	220-239-6	
Concentration	< 0,0015	%

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 3	H301
Acute Tox. 2	H330
Skin Corr. 1B	H314
Eye Dam. 1	H318
Aquatic Acute 1	H400
Skin Sens. 1A	H317
Aquatic Chronic 1	H410
Acute Tox. 3	H311

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1A	H317	>= 0,0015
Aquatic Acute 1	H400	M = 10

SECTION 4: First aid measures**4.1. Description of first aid measures****After skin contact**

Wash with plenty of water and soap. Do NOT use solvents or thinners.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). In case of irritation consult an oculist.



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

After ingestion

Rinse mouth thoroughly with water. If larger amounts are swallowed or in the event of symptoms take medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide, Foam, Sand, Water

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); dense black smoke

5.3. Advice for firefighters

Other information

Collect contaminated fire-fighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No particular measures required.

6.2. Environmental precautions

No particular measures required.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid skin and eye contact. Smoking, eating and drinking shall be prohibited in application area.

Advice on protection against fire and explosion

No special measures required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in frostfree conditions.

7.3. Specific end use(s)

Paint

SECTION 8: Exposure controls/personal protection ***



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

8.1. Control parameters

Other information

There are not known any further control parameters.

Derived No/Minimal Effect Levels (DNEL/DMEL) ***

Bronopol (INN)

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	4,1	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	12,3	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	4,2	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	4,2	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	2,3	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	7	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Local effects	
Concentration	13	µg/cm ²
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Local effects	
Concentration	13	µg/cm ²
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1,2	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	3,7	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	1,3	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	1,3	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	1,4	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	4,2	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Local effects	
Concentration	8	µg/cm ²
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	dermal	



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

Mode of action	Local effects	
Concentration	8	µg/cm²
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	0,35	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	1,1	mg/kg/d

Predicted No Effect Concentration (PNEC) ***

Bronopol (INN)

Type of value	PNEC	
Type	Freshwater	
Concentration	0,01	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,001	mg/l
Type of value	PNEC	
Type	Water (intermittent release)	
Concentration	0,003	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	0,43	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,041	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,003	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,5	mg/kg

8.2. Exposure controls

Exposure controls

Provide adequate ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form liquid



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

Colour	coloured
Odour	odourless
Odour threshold	
Remarks	No data available
pH value	
Value	8 to 9
Temperature	20 °C
Method	WTW PH 340
Melting point	
Remarks	not determined
Freezing point	
Remarks	not determined
Initial boiling point and boiling range	
Value	appr. 100 °C
Pressure	1.013 hPa
Source	Literature value
Flash point	
Remarks	Not applicable
Evaporation rate (ether = 1) :	
Remarks	not determined
Flammability (solid, gas)	
Not applicable	
Upper/lower flammability or explosive limits	
Remarks	not determined
Vapour pressure	
Value	appr. 23 hPa
Temperature	20 °C
Method	Value taken from the literature
Vapour density	
Remarks	not determined
Density	
Value	1,04 g/cm ³
Temperature	20 °C
Method	DIN EN ISO 2811
Solubility in water	
Remarks	miscible
Ignition temperature	
Remarks	not determined
Viscosity	
Remarks	
Remarks	not determined

9.2. Other information**Other information**

None known

SECTION 10: Stability and reactivity**10.1. Reactivity**



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

None

10.2. Chemical stability

No hazardous reactions known.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

No hazardous reactions known.

10.5. Incompatible materials

None

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity

Remarks Based on available data, the classification criteria are not met.

Acute oral toxicity (Components)

1,2-Benzisothiazol-3(2h)-one

Species	rat		
LD50		1193	mg/kg

Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity (Components)

1,2-Benzisothiazol-3(2h)-one

Species	rat		
LD50		4115	mg/kg

Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Remarks Based on available data, the classification criteria are not met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Remarks Based on available data, the classification criteria are not met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

Aspiration hazard

Based on available data, the classification criteria are not met.

Experience in practice

Provided all the recommended protective and safety precautions are taken, experience shows that no risk to health can be expected.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

SECTION 12: Ecological information**12.1. Toxicity****General information**

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

Fish toxicity (Components)**1,2-Benzisothiazol-3(2h)-one**

Species	rainbow trout (<i>Oncorhynchus mykiss</i>)		
LC50	2,18		mg/l
Duration of exposure	96	h	

Bronopol (INN)

Species	rainbow trout (<i>Oncorhynchus mykiss</i>)		
LC50	3		mg/l
Duration of exposure	96	h	
Method	OECD 203		

Bronopol (INN)

Species	rainbow trout (<i>Oncorhynchus mykiss</i>)		
NOEC	2,61		mg/l
Duration of exposure	28	d	
Method	OECD 203		

Daphnia toxicity (Components)**1,2-Benzisothiazol-3(2h)-one**

Species	Daphnia magna		
EC50	2,94		mg/l
Duration of exposure	48	h	

Bronopol (INN)

Species	Daphnia magna		
EC50	1,04		mg/l
Duration of exposure	48	h	
Method	OECD 202		

Bronopol (INN)

Species	Daphnia magna		
NOEC	0,06		mg/l
Duration of exposure	21	d	
Method	OECD 211		

Algae toxicity (Components)**1,2-Benzisothiazol-3(2h)-one**

Species	Pseudokirchneriella subcapitata		
ErC50	0,11		mg/l
Duration of exposure	72	h	



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

Bronopol (INN)

Species	Pseudokirchneriella subcapitata	
EC50	0,068	mg/l
Duration of exposure	72	h
Method	OECD 201	

Bronopol (INN)

Species	Pseudokirchneriella subcapitata	
NOEC	0,0025	mg/l
Duration of exposure	72	h
Method	OECD 201	

12.2. Persistence and degradability

General information

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

The product can be placed with other household refuse. Small residues in containers can be washed-out with water and put into the drainage system.

Disposal recommendations for packaging

Packaging that cannot be cleaned should be disposed off as product waste. Completely emptied packagings can be given for recycling.

SECTION 14: Transport information

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	The product does not constitute a hazardous substance in land transport.-	The product does not constitute a hazardous substance in sea transport.-	The product does not constitute a hazardous substance in air transport.-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
Subsidiary risk		-	-
Label			
14.4. Packing group	-	-	-
Transport category	0		
14.5. Environmental hazards	-	no	-

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:
 Always transport in closed containers that are upright and secure.
 Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

no

SECTION 15: Regulatory information ***

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Other information

All components are contained in the IECSC inventory.
 All components are contained in the ECL inventory.
 All components are contained in the TSCA inventory or exempted.

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.



Trade name: Porcelain&GlasPainterSor.Basic 125

Version: 9 /

Date revised: 12.12.2019

Substance number: 012300080-125

Replaces Version: 8 / WORLD

Print date: 14.12.19

H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Eye Dam. 1	Serious eye damage, Category 1
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1A	Skin sensitization, Category 1A
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***
 This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.
 The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.
 The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.