Trade name: Marabu Textil Metallic 784, 50 ml

Date revised: 06.05.2020 Version: 6 /

Print date: 07.05.20 Substance number: 171405784 Replaces Version: 5 / WORLD

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Marabu Textil Metallic 784, 50 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

1.3. Details of the supplier of the safety data sheet

Address/Manufacturer

Marabu GmbH & Co. KG Asperger Strasse 4 71732 Tamm Germany

Telephone no. +49-7141/691-0 Fax no. +49-7141/691-147

Information provided Department product safety

by / telephone

E-mail address of

person responsible

PRSI@marabu.com

for this SDS

Importer -

S&S Wholesale Pty. Limited 18/10 Pioneer Avenue, Thornleigh NSW 2120

Tel: 1300 731 529 Fax: 1300 739 715

Emergency Contact:

S&S Wholesale Pty. Limited

Tel: 1300 731 529 Fax: 1300 739 715

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification ***

2.1. Classification of the substance or mixture

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

EUH208 Contains 2-Methyl-2H-isothiazol-3-one, A mixture of:

5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and

2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1).

1,2-Benzisothiazol-3(2h)-one, May produce an allergic reaction.

Supplemental information

Labelling according to regulation (EU) No 528/2012 ***

Contains a biocidal product: A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and 2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1)

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients ***

3.2. Mixtures

Chemical characterization

Paint based on water

Hazardous ingredients ***

Trade name: Marabu Textil Metallic 784, 50 ml

Version: 6 / Date revised: 06.05.2020

Substance number: 171405784 Replaces Version: 5 / WORLD Print date: 07.05.20

2,2'-Oxybisethanol

CAS No. 111-46-6 EINECS no. 203-872-2

Registration no. 01-2119457857-21

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H302

Pyridin-2-thiol-1-oxide, sodium salt

CAS No. 3811-73-2 EINECS no. 223-296-5

Concentration >= 0,001 < 0,1 %

Classification (Regulation (EC) No. 1272/2008)

Eye Dam. 1 H318 Acute Tox. 4 H302 Acute Tox. 4 H332 Aquatic Acute 1 H400 Aquatic Chronic 2 H411

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1 H400 M = 100

1,2-Benzisothiazol-3(2h)-one

CAS No. 2634-33-5 EINECS no. 220-120-9

Concentration < 0.05 %

Classification (Regulation (EC) No. 1272/2008)

Aquatic Acute 1 H400
Skin Sens. 1 H317
Acute Tox. 4 H302
Skin Irrit. 2 H315
Eye Dam. 1 H318
Acute Tox. 2 H330
Aquatic Chronic 2 H411

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317 >= 0,05

A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and 2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1)

CAS No. 55965-84-9

Concentration >= 0.001 < 0.0015 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 2 H330
Aquatic Chronic 1 H410
Aquatic Acute 1 H400
Skin Sens. 1A H317
Skin Corr. 1C H314
Acute Tox. 2 H310
Acute Tox. 3 H301

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Corr. 1C H314 >= 0,6 Eye Irrit. 2 H319 <= 0,06 < 0,6 Skin Irrit. 2 H315 <= 0,06 < 0,6

Trade name: Marabu Textil Metallic 784, 50 ml

Version: 6 / Date revised: 06.05.2020

Substance number: 171405784 Replaces Version: 5 / WORLD Print date: 07.05.20

Skin Sens. 1 H317 \Rightarrow 0,0015 Aquatic Acute 1 H410 M = 100 Aquatic Chronic H410 M = 100

1

2-Methyl-2H-isothiazol-3-one

CAS No. 2682-20-4 EINECS no. 220-239-6

Concentration < 0,0015 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 3 H301 Acute Tox. 2 H330 Skin Corr. 1B H314 Eye Dam. 1 H318 Aquatic Acute 1 H400 Skin Sens. 1A H317 Aquatic Chronic 1 H410 Acute Tox. 3 H311

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1A H317 >= 0,0015Aquatic Acute 1 H400 M = 10

SECTION 4: First aid measures

4.1. Description of first aid measures

After skin contact

Wash with plenty of water and soap. Do NOT use solvents or thinners.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). In case of irritation consult an oculist.

After ingestion

Rinse mouth thoroughly with water. If larger amounts are swallowed or in the event of symptoms take medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide, Foam, Sand, Water

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); dense black smoke; Nitrogen oxides (NOx)

5.3. Advice for firefighters

Other information

Collect contaminated fire-fighting water separately, must not be discharged into the drains.

Trade name: Marabu Textil Metallic 784, 50 ml

Version: 6 / Date revised: 06.05.2020

Substance number: 171405784 Replaces Version: 5 / WORLD Print date: 07.05.20

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No particular measures required.

6.2. Environmental precautions

No particular measures required.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid skin and eye contact. Smoking, eating and drinking shall be prohibited in application area.

Advice on protection against fire and explosion

No special measures required.

Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires B (Combustible liquid substances)

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in frostfree conditions.

7.3. Specific end use(s)

Paint

SECTION 8: Exposure controls/personal protection ***

8.1. Control parameters

Biological limit values

Fluorphlogopite

List TRGS 903 Value 7

Value 7 mg/g creatinine

Parameter Fluorine Testing material Urine (U)

Test date End of exposure or end of shift.

Fluorphlogopite

List TRGS 903
Value 4 mg/g
creatinine

Great

Parameter Fluorine Testing material Urine (U)

Test date Before next shift.

Other information

There are not known any further control parameters.

Derived No/Minimal Effect Levels (DNEL/DMEL) ***

Trade name: Marabu Textil Metallic 784, 50 ml

Version: 6 / Date revised: 06.05.2020

Substance number: 171405784 Replaces Version: 5 / WORLD Print date: 07.05.20

2,2'-Oxybisethanol

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Local effects

Concentration 60 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 43 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Local effects

Concentration 12 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 21 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 44 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consumer

Long term

inhalative

Local effects

Concentration 12 mg/m³

Predicted No Effect Concentration (PNEC) ***

2,2'-Oxybisethanol

Type of value PNEC
Type Freshwater

Concentration 10 mg/l

Type of value PNEC Saltwater

Concentration 1 mg/l

Type of value PNEC

Type Water (intermittent release)

Concentration 10 mg/l

Trade name: Marabu Textil Metallic 784, 50 ml

Version: 6 / Date revised: 06.05.2020

Substance number: 171405784 Replaces Version: 5 / WORLD Print date: 07.05.20

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 199,5 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 20,9 mg/kg

Type of value PNEC

Type Marine sediment

Concentration 2,09 mg/kg

Type of value PNEC Type Soil

Concentration 1,53 mg/kg

8.2. Exposure controls

Exposure controls

Provide adequate ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form liquid coloured Odour odourless

Odour threshold

Remarks No data available

pH value

Value 7 to 9 Temperature 20 °C

Method WTW PH 340

Melting point

Remarks not determined

Freezing point

Remarks not determined

Initial boiling point and boiling range

Value appr. 244,9 °C

Pressure 1.013 hPa

Source Literature value

Flash point

Remarks Not applicable

Evaporation rate (ether = 1):

Remarks not determined

Flammability (solid, gas)

Not applicable

Upper/lower flammability or explosive limits

Remarks not determined

Vapour pressure

Value appr. 23 hPa

Temperature 20 °C

Trade name: Marabu Textil Metallic 784, 50 ml

Version: 6 / Date revised: 06.05.2020

Substance number: 171405784 Replaces Version: 5 / WORLD Print date: 07.05.20

Method Value taken from the literature

Vapour density

Remarks not determined

Density

Value 1,15 g/cm³

Temperature 20 °C

Method DIN EN ISO 2811

Solubility in water

Remarks miscible

Ignition temperature

Remarks not determined

Viscosity

Value 16000 to 26000 mPa.s

Temperature 20 °C

Method Brookfield

Efflux time

Value 200 s

Method DIN 53211 4 mm

9.2. Other information

Other information

None known

SECTION 10: Stability and reactivity

10.1. Reactivity

None

10.2. Chemical stability

No hazardous reactions known.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

No hazardous reactions known.

10.5. Incompatible materials

None

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity

ATE > 2.000 mg/kg Method calculated value (Regulation (EC) No. 1272/2008)

Acute oral toxicity (Components)

1,2-Benzisothiazol-3(2h)-one

Species rat

LD50 1193 mg/kg

2,2'-Oxybisethanol

Trade name: Marabu Textil Metallic 784, 50 ml

Version: 6 / Date revised: 06.05.2020

Substance number: 171405784 Replaces Version: 5 / WORLD Print date: 07.05.20

Species Rats (male/female)

LD50 > 1000 mg/kg

Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity (Components)

1,2-Benzisothiazol-3(2h)-one

Species rat

LD50 4115 mg/kg

Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Remarks Based on available data, the classification criteria are not met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Remarks Based on available data, the classification criteria are not met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Experience in practice

Provided all the recommended protective and safety precautions are taken, experience shows that no risk to health can be expected.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself.Do not allow to enter drains or water courses.The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

Fish toxicity (Components)

A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and 2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1)

Species rainbow trout (Oncorhynchus mykiss)

Trade name: Marabu Textil Metallic 784, 50 ml

Version: 6 / Date revised: 06.05.2020

Substance number: 171405784 Replaces Version: 5 / WORLD Print date: 07.05.20

LC50 0,188 mg/l

Duration of exposure 96 h

1,2-Benzisothiazol-3(2h)-one

Species rainbow trout (Oncorhynchus mykiss)

LC50 2,18 mg/l

Duration of exposure 96 h

Daphnia toxicity (Components)

A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and

2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1)

Species Daphnia magna

EC50 0,126 mg/l

Duration of exposure 48 h

1,2-Benzisothiazol-3(2h)-one

Species Daphnia magna

EC50 2,94 mg/l

Duration of exposure 48 h

Algae toxicity (Components)

A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and

2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1) / C(M)IT/MIT (3:1)

Species Selenastrum capricornutum

EC50 0,027 mg/l

Duration of exposure 72 h

1,2-Benzisothiazol-3(2h)-one

Species Pseudokirchneriella subcapitata

ErC50 0,11 mg/l

Duration of exposure 72 h

12.2. Persistence and degradability

General information

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Do not allow to enter drains or water courses.

Dispose of waste according to applicable legislation.

Trade name: Marabu Textil Metallic 784, 50 ml

Version: 6 / Date revised: 06.05.2020

Substance number: 171405784 Replaces Version: 5 / WORLD Print date: 07.05.20

Dispose of as hazardous waste.

Disposal recommendations for packaging

Packaging that cannot be cleaned should be disposed off as product waste.

Completely emptied packagings can be given for recycling.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	The product does not constitute a hazardous substance in land transport	The product does not constitute a hazardous substance in sea transport	The product does not constitute a hazardous substance in air transport
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
Subsidiary risk		-	-
Label			
14.4. Packing group	-	-	-
Transport category	0		
14.5. Environmental hazards		no	
. 160 =110 01110 1110 1110 1100 1100	-		-

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

nc

SECTION 15: Regulatory information ***

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Other information ***

The product does not contain substances of very high concern (SVHC).

Other information

All components are contained in the TSCA inventory or exempted.

All components are contained in the DSL or NDSL inventory.

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

Trade name: Marabu Textil Metallic 784, 50 ml

Version: 6 / Date revised: 06.05.2020

Substance number: 171405784 Replaces Version: 5 / WORLD Print date: 07.05.20

SECTION 16: Other information

Hazard statements listed in Chapter 3

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.
H332 Harmful if inhaled.
Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 2 Acute toxicity, Category 2
Acute Tox. 3 Acute toxicity, Category 3
Acute Tox. 4 Acute toxicity, Category 4

Aquatic Acute 1 Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic, Category 2

Eye Dam. 1

Skin Corr. 1B

Skin corrosion, Category 1B

Skin Corr. 1C

Skin corrosion, Category 1C

Skin Irrit. 2

Skin irritation, Category 2

Skin Sens. 1

Skin sensitization, Category 1

Skin Sens. 1A

Skin sensitization, Category 1A

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: *** This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship. The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.